

KRAMER
vic.
J. Clark Salyer National Wildlife Refuge, Dam 332
Along the Lower Souris River
Bottineau County
McHenry County
North Dakota

HAER No. ND-4-C

HAER
ND,
5-KRAM,
1-C-

PHOTOGRAPHS

WRITTEN HISTORICAL AND DESCRIPTIVE DATA

Historic American Engineering Record
Rocky Mountain Regional Office
National Park Service
U.S. Department of the Interior
12795 W. Alameda Parkway
Denver, Colorado 80225

HISTORIC AMERICAN ENGINEERING RECORD

J. Clark Salyer National Wildlife Refuge, Dam 332

HAER No. ND-4-C

Location: Along the Lower Souris River, in the J. Clark Salyer National Wildlife Refuge,
Bottineau and McHenry Counties, North Dakota
KRAMER V.C.
UTM: NE End: 48 degrees, 40' 28" (lat.); 100 degrees, 46' 30" (long.)
SW End: 48 degrees, 40' 14" (lat.); 100 degrees, 47' 36" (long.)
Quad: Deep

Date of Construction: 1935-1936

Present Owner: U.S. Fish and Wildlife Service

Present Use: Damming Souris River

Significance: The dams within the J. Clark Salyer National Wildlife Refuge represent a historical movement to preserve wildlife and wildlife habitat in the United States, which began in the mid-19th century and continues today. The refuge dams are significant for their association with the development of the national wildlife refuge system during the New Deal Era. At the time of its creation, the J. Clark Salyer Wildlife Refuge was considered the most important project in the Federal Government's program of migratory waterfowl habitat restoration. The dams also are representative examples of dams designed by the Federal Government during the New Deal Era for conservation projects.

Historians: Frederick L. Quivik, RTI, Inc., August 1989
Mary E. McCormick, RTI, Inc., August 1989
Jane L. Carroll, St. Paul District Corps of Engineers, March 1990

For more historical information, see J. Clark Salyer National Wildlife Refuge Dams, HAER No. ND-4

HAER
ND,
5-KRA.V,
1-C-

J. CLARK SALYER NATIONAL WILDLIFE REFUGE DAMS (Lower Souris National Wildlife Refuge)

The J. Clark Salyer National Wildlife Refuge is located along a winding 75-mile stretch of the Souris River in Bottineau and McHenry counties in north-central North Dakota. Originally established in the mid-1930s as the Lower Souris National Wildlife Refuge, this refuge was renamed in 1967 in honor of J. Clark Salyer, II, the chief of the national wildlife refuge program from 1934-1961. The 58,700-acre refuge is largely comprised of native prairie lands, with some wooded bottom lands and aspen and brush-covered sandhills, as well as over 21,000 acres of restored river ponds, marshes, and wet meadows. Water developments in the refuge were established and are maintained by a network of five major dams and other diversion structures, including two small masonry dams and several dikes, levees and channels. The five major dams are located so that their reservoirs or backwaters extend nearly the entire length of the refuge, from near Upham north to the United States-Canada border. The headquarters for the refuge are situated west of the river, about two miles north-northeast of the town of Upham, and adjacent to one of the southernmost dams, Dam 326. Access to the refuge headquarters from Upham is provided by a county highway.

DAM 332

Dam 332 is located about 3-1/2 miles northwest, or downstream, of the refuge headquarters near Dam 326 (n 1/2 Sec. 19 and NW 1/4 Sec. 20, T160N, R78W) and is situated in Bottineau County.

Dam 332 is a homogeneous earthfill embankment, emergency spillway, and outlet works. The earthfill embankment is oriented along a northeast/southwest axis, and has a height of about 13 feet, a crest width of 15 feet, a crest width of 12 feet, and a crest elevation of 1,422 feet. The total length of the embankment, including the spillway, is 4,954 feet. The upstream side of the embankment has a slope of 5:1 along its upper section and a slope of 10:1 along its lower section. The downstream side of the embankment has a slope of 4:1. The surface of the embankment is vegetated with grass. Original plans for the dam called for the top soils at the site to be plowed before construction of the embankment. Earthfill for the embankment was apparently excavated from a nearby location. [1]

The emergency spillway is an uncontrolled weir located along the crest of the embankment about 2,700 feet southeast of the left abutment. When originally constructed, the spillway was a 700-foot-long stone masonry wall with flared stone-masonry wing walls and a stone masonry apron below its downstream edge. Since then, most likely in the late 1940s, the stone masonry wall was modified by the addition of a concrete cap and concrete buttresses that are spaced about 12 feet on center along the wall's downstream face. [2] The current crest elevation of the weir is 1,419.1 feet.

The outlet works are located at the southwest end of the dam and consist of a reinforced concrete structure with three radial gates. The concrete structure is comprised of four, 16-foot-long by 15-foot-high walls (two end walls and two piers), that serve to support the radial gates. The downstream wing walls for the concrete structure are constructed of interlocking, corrugated sheet piling, and the upstream wing walls are concrete.

The radial gates each consist of a corrugated steel face (16 feet wide by 9 feet high) with channel-section supports and angle-section radials. The outer face of each gate is set along the upstream side of the concrete structure. There is no intake to the gates; however, the concrete walls between the gates extend downstream and serve as outlet structures. The outlets discharge into a stilling basin that consists of a plunge pool with a concrete apron.

Manual hoists operate the radial gates. The hoist control for each gate is mounted on top of an adjacent concrete wall. Access to the hoist controls is provided by a cantilevered walkway along the structure's upstream side. The walkway is secured to the structure by angle-section knee-braces and consists of a plank deck and an angle-section rail. Along its downstream side, the concrete structure also supports a concrete beam walkway that is protected by angle-section railing. In 1949, the original height of the concrete structure was raised 3 feet by concrete caps that were added to the top of each of the end walls and piers, as well as both of the upstream wing walls. At the same time, the gate hoist controls, and the upstream and downstream walkways, were removed and reinstalled in their current locations. [3]

FOOTNOTES

- 1 Marshall Fox and Terry Clayton, "Inspection Report, J. Clark Salyer Dam #332, J. Clark Salyer National Wildlife Refuge, Bottineau County, North Dakota, Federal Inventory number ND 00326," p. 10, report prepared for the U.S. Fish and Wildlife Service, June 1984.
- 2 John F. Reiger, American Sportsmen and the Origins of Conservation, Norman: University of Oklahoma Press, 1975, p. 21
- 3 Ibid., p. 51.